(54) Title: SYSTEM AND METHOD FOR RECORDING VOICE AND THE DATA ENTERED BY A CALL CENTER AGENT AND RETRIEVAL OF THESE COMMUNICATION STREAMS FOR ANALYSIS OR CORRECTION

(57) Abstract: The invention provides for a communications recording and analysis system including means for recording one or more communication streams, means for identifying the recorded stream, means for retrieving the content of said recordings by identifier tags, and wherein additional real-time information is inferred from analysis, in real-time or later, of keystrokes entered at a computer/terminal handling the interaction, and/or computer mouse actions, and/or internet traffic emanating from, or terminating at, any one or more of a number of computers/terminals handling the interaction, and/or the words and/or prosody spoken during the interaction is recorded. Furthermore graphical display means are provided such that the presentation of call flow recording is in the form of a direct graph showing the progress of the calls through the various states and transitions.

SYSTEM AND METHOD FOR RECORDING VOICE AND THE DATA ENTERED BY A CALL CENTER AGE
NT AND RETRIEVAL OF THESE COMMUNICATION STREAMS FOR ANALYSIS OR CORRECTION

The present invention relates to a system and method for
5   analysing communication streams.

Currently many commercial entities perform substantial
amounts of their business via telephone or Internet contact
with their customers. The analysis of such contact can
10   therefore help businesses to improve the quality and
efficiency of their services, and assist with customer
retention and, ultimately, profitability. Attempts have
been made previously to achieve such analysis in a
satisfactory manner and to a satisfactory degree. For
15   example, many businesses have, for some time, recorded some
of their communications streams e.g. telephone calls between
their staff and their customers. Traditionally this was
done to satisfy regulatory requirements or to help resolve
disputes. More recently, the emphasis has moved towards the
20   reviewing of these interactions from a quality perspective.
This is intended to identify good and bad aspects of
particular calls with a view to improving the level of
customer service given. Recently, for example, recording
the activity on a PC screen has been undertaken to improve
25   the completeness of the review procedure with the reviewer
able to see how accurately staff are entering information
received via the telephone.

Also, it has been known to employ Call Detail Recording
30   (CDR) systems to prevent perceived abuse of telephone
systems and to apportion costs to the department or
individual making the calls.

Originally such records were printed out directly from the
35   Private Automatic Branch Exchange (PABX) onto a line
printer. Later, systems were designed to store this
information in a database allowing more sophisticated

reporting and searching for calls on the basis of one or more of the stored call details. More recently, Computer Telephony Integration (CTI) interfaces have been provided that give this information in real-time, during the call.

Further, several systems currently exist that use call recording in combination with CDR or CTI and a database application in order to perform routine monitoring of calls with the intention of identifying weaknesses in individual Customer Service Representatives (CSRs). Typically a small percentage of the CSR calls are reviewed and "scored" against a set of predetermined criteria to give an indication of the quality of that particular member of staff.

Within a call-centre environment, it should also be noted that rather than simply using standard PC office automation applications when dealing with customers, staff in most call centres use increasingly sophisticated applications that help them to handle the calls more efficiently and effectively. Helpdesk applications and telemarketing call scripting applications are examples of such applications. Most such applications share the following characteristics:

(i) they guide the staff member through the interaction, either explicitly suggesting questions to ask or implicitly e.g. by presenting a form with various fields to be filled in with details to be gleaned from the customer; and

(ii) the progress of the call is, to some degree, dictated by the answers given during the call.

As an example, a service call to a help desk may flow through the following stages:

(i) take customer details and verify maintenance contract is up to date;

(ii) take details of the problem being experienced;

(iii) attempt to resolve using appropriate set of

3

diagnostic questions;

      (iv) if not solved, agree schedule for engineer to visit; and

      (v)   give customer a problem reference number.

Within each of the above main stages there will be one or more sub-stages e.g. (i)(a) caller's name (i)(b) zip code etc.

Current systems employed for CSR quality monitoring require the manual review of calls in order to determine a quality "score". This prohibits the review of more than a few percent of all calls and the accuracy of the human scoring process and its objectivity are at best questionable. When coupled with a small sample size of typically only a few calls per CSR per week, the resultant scores offer a limited degree of quality monitoring. Also there are only a few aspects of the call that allow for automated scoring. The most common such aspect is the call duration which, for a known telemarketing script, should be within a known range. A portion of the overall score (perhaps 5%) may be allocated to such an aspect of the call.

Call centre management seeks to handle calls as efficiently as possible yet take advantage of cross-selling and up-selling opportunities whilst the customer is already on the line. To this end, the way in which calls are handled within the call centre is of critical importance to the overall efficiency and profitability of the operation. As the sophistication of call handling systems and processes increases, so the complexity of the call flow designs increases such that it is very difficult to fully test and exercise these "scripts" prior to, or even during, their full-scale deployment. Sophisticated scripts may require a hundred pages or more of documentation including the "call flow diagram" and the associated questions and forms presented to the CSR. With many hundreds or even thousands

4

of possible paths through such a script, any one CSR will
not have sufficient experience of many particular routes
through the script to allow for the objective evaluation of
the effectiveness or otherwise of, for example, the
5   suggested way to handle a particular objection raised during
a sale.

Current systems typically store details of each call in a
relation database typically with one record of more or less
10 fixed structure per call.   These details may include
indications of the type of call, the "completion code", or
whether a particular option was chosen or not etc.   More
advanced systems cater for the cases where a single "call"
actually contains more than one transaction (e.g. request a
15 quotation for two different insurance policies).   This is
typically done by subdividing the call into two or more
parts each of which then has a database record associated
with it.

20 Existing systems use one or more database records per call
and the identification of calls normally requires that the
user determine in advance which aspects of the call's
progress are to be stored.   Timing information stored is
often limited to total call duration.   The relative time
25 between different points in the call is difficult to
determine.   Calls that "loop" through the same part of the
script several times are not well described by a single
database record.

30 It has also been appreciated that customers and potential
customers generally much prefer a "warm call" to a "cold
call" i.e. a call where the caller obviously has taken the
trouble to find out about a customer's previous dealings
with their business rather than merely selecting the name
35 from a list without any knowledge of the particular
customer's details;   many of which may already have been
given previously.

5

Many businesses now proactively call their customers on a regular basis to try and "cross-sell" or "up-sell" with other products that they have determined may be of interest to the customer.

5

However, currently, where a follow-up call is to be made as the result of a previous call perhaps made several months earlier there is often little information available to the CSR responsible for the follow-up call. For example, a
10 routine call to all mortgage customers may include the question "Have you reviewed your life insurance cover recently"?. According to the answer given, the customer may be placed on a list for a follow up call the next time a new life insurance policy is launched. At the time of the
15 original call, the CSR will likely do no more than tick a "Yes/No/Maybe" option.

When the customer is called some months later, all that the new agent knows is that the customer previously said they
20 may have been interested and the factual details presented about the customer's previous purchasing history. They do not know exactly how or in what tone of voice the customer responded several months earlier.

25 Additionally, such systems are open to abuse by the CSRs as they may be rewarded, or at least measured, by the number of such follow-up leads they record. Hence there is a temptation for anything other than a point-blank "No" to be recorded as a "Maybe".
30

It is also acknowledged that, in order to improve business processes, train CSRs and identify problems, there is a desire to identify individual calls or sets of calls which are handled particularly well or badly or that highlight
35 deficiencies, opportunities, trends or anomalies.

Existing systems limit the selection criteria to those that

6

can be derived solely from call details. These use
individual database records associated with each call to
store data fields about each call. These are particularly
inflexible and need to be designed prior to the query. For
5 example, if a user identifies that they will want to search
for calls where the "Help" key was pressed, they could tag
each call with a binary flag and set this to true as the
help key is pressed. A more sophisticated solution would be
to use a time field and store the time at which the help key
10 was pressed. However, if the user then wants to find calls
where "Help" was pressed twice or more, this known previous
database scheme proves inadequate.

When considering call-replay, and irrespective of the reason
15 for wanting to replay a specific call, there is often a
desire to listen to a particular section of a call rather
than the whole call. For example, an insurance claims
handler will want to confirm that a driver now known to have
a previous conviction disclosed this when asked during the
20 initial policy quotation. Being able to jump directly to
the portion of the call where the customer was asked this
question avoids the need to browse through the whole call.
Alternatively, a mail-order company CSR needing to correct
an invalid address would like to jump to the part of the
25 original call where the address was given.

Current systems require users to either listen to the whole
call or to jump around the call listening to snippets until
they "home in" on the required section. This is time
30 consuming and prone to error.

Further it has long been possible to perform automated
speech recognition in an attempt to transcribe or at least
to highlight key words within telephone conversations. The
35 capabilities of such systems (accuracy, tolerance of natural
conversation speed, cost effectiveness) have been gradually
improving during recent years.

7

To obtain maximum accuracy, currently employed algorithms are very CPU and memory intensive. It is unlikely that many customers will be able to afford to deploy full recognition across all conversations they record.

5

Simply applying generic recognition to the whole of a conversation requires the recognition algorithm to infer the context and grammar from the conversation in order to refine its decisions as to which words it heard. This process is

10 CPU intensive and less accurate than being explicitly told the current context of the conversation.

It will therefore be appreciated that the current schemes of communication analysis are disadvantageously limited.

15

The present invention seeks to provide a system and method for analysing communication streams having advantages over known such systems and methods.

20 According to one aspect of the present invention there is provided a system for communications recording and analysis including means for recording one or more communication streams, means for identifying the recorded streams, means for retrieving the content of said recordings· by identifier

25 tags and wherein additional real-time information relating to the progress of the said communication streams is recorded.

Preferably, the communication streams and associated

30 progress streams are linked by means of a cross reference within respective call detail records in a database of recordings. .

In one embodiment, the communication streams can be

35 interleaved with the call flow recordings and a composite stream is recorded.

8

Advantageously, the progress information may be inferred from analysis, in real-time or later, of keystrokes entered at a computer/terminal handling the interaction.

5   Alternatively, the progress information may be inferred from analysis, in real-time or later, of computer mouse actions.

Yet further, the progress information may be inferred from analysis, in real-time or later, of internet traffic
10 emanating from, or terminating at, any of a number of computers/terminals handling the interaction.

Additionally, the progress information may be inferred from analysis, in real-time or later, of the words and/or prosody
15 spoken during the interaction.

It should be appreciated that the contents of the call flow data stream may be used to refine the recording and/or analysis of the main stream(s).
20
Preferably, retrieval of specific sets of recordings may be performed by selection from the call detail records describing each of the recordings and/or the presence, repeated presence or absence of specified events or call
25 states.

Advantageously, the criteria may include relative or absolute timing information.

30 Further, the presentation of the content of individual recordings may be in the form of a graphical display including bars and/or pictures and wherein the location, colour and/or size of which may be determined by the recorded call flow recording.
35
In particular, the presentation of one or more call flow recordings may be in the form of a directed graph showing

9

the progress of the calls through the various states and transitions.

Also, the position, colour, labelling, texture and other
5   graphical attributes of the nodes and/or lines can be
determined by the number of calls following that route; the
time they spend in the various states and/or other
attributes derivable from the call flow recordings.

10 Still further, the display can be populated, and the
graphical attributes modified, in real-time to reflect the
timing information recorded within the call flow recordings.

In particular, the speed of replay can be varied, for
15 example, including "paused", "forwarded" or "reversed" at
any rate including "single-step" mode.

Also, the set of call flow recordings may be refined by
selecting, for example, via a double-click, a specific
20 transition as discussed further later.

Advantageously, specific nodes and/or transitions can be
highlighted according to automatically or manually defined
rules so as to draw attention to the presence or absence of
25 particular call flow routes.

The invention is advantageous in that the ability to track
the progress of the call through the various stages allows
more criteria to be subsequently scored automatically and
30 hence objectively. Since computer-scoring can be easily and
cost effectively achieved, it can be performed economically
on a much larger sample of the calls - often the full 100%.
For example, the time spent taking customer details should
be within allowed ranges. Calls that did not result in the
35 sale of product "X" should not have spent more than t
seconds trying to sell this product before moving on to
other propositions. Calls should not occur where the

10

customer had to go back and re-enter details that should
have been picked up earlier. Such a system allows perhaps
20-30% of the overall quality "score" to be determined
automatically and therefore objectively and across all
5   calls. This gives much better statistical significance with
less manpower.

With regard to call flow design and call centre management,
the invention can for example:
10   present N examples of calls following a specific
                path through the call flow script e.g. a rarely
                exercised branch; and
                further filter these calls according to more
                traditional call detail records e.g. "Service
15   calls for Model XYZ that ended without problem
                resolution"

Having selected the set of calls of interest, these are then
presented to the user and this can allow them to:
20   review just a specified section of the call (e.g.
                answer to question 143) without having to dip into
                the whole call to determine the appropriate part
                of the call;
                review the whole call so as to hear the required
25   section in context; and
                see the timing information associated with the
                calls e.g. how long spent in the specified
                section; how long between start of sales pitch and
                this section etc.
30
Turning now to the personalisation of calls, the invention
can advantageously allow the few seconds of response to the
relevant question to be retrieved efficiently without the
user having to listen to the rest of the call. Using this
35   feature, two strategies can be adopted. First, all of the
responses to the question can be reviewed by a dedicated
individual or team prior to the campaign getting underway.

As they listen to all of the responses, they can (a)
prioritise the customers from most to least likely to buy
and hence choose which ones will eventually be called and
(b) ensure that the script that is to be used when the
5   campaign starts includes answers to the issues likely to be
raised.   Hence they can improve the effectiveness of the
campaign and reduce the number of wasted calls that will be
made.   Note that feature (a) above requires all responses to
be listened to, whilst feature (b) only requires that a
10   statistically significant sample be reviewed.

Secondly, during the campaign, agents may be presented with
the previous response either in audio form or in textual
form (manually or automatically transcribed).   The former
15   gives them the tonal and emotional content of the response
but is less practical where autodiallers are used to present
calls to CSRs as soon as the customer answers.   Either
approach lets them speak to the customer from a position of
advantage, knowing exactly how they reacted to the question
20   when last asked.   Presenting the previous response first
would allow the CSR to determine whether it is worth placing
the call or not.

By recording the detailed progress of the call along with
25   the call details and call content, the system advantageously
allows the user to identify sets of "interesting" calls.
Such calls might be those exhibiting the presence or absence
of certain events within the call e.g. CSR requested "help"
during the quotation process.   This could identify CSR
30   specific training needs or areas where all staff experience
difficulty that could be improved.

Alternatively, or in addition, where one product was
purchased but details of others were also given, it might be
35   worth calling the customer soon to try again to sell them
these other products.

12

Also, where the CSR had to return to a previous part of the
script, the reason for this can be considered. For example,
was a question ambiguous, a mistake made or did the customer
change their mind?

5

Further, where less than 5 seconds was spent in the
"confirmation" screen where customers should have the small
print explained to them, this could suggest that the CSR was
rushing on to the next call too fast.

10

Of course, poor typing skills might be indicated by
excessive corrections and slow data entry.

Efficient replay of calls can advantageously be achieved by
15   recording the detailed progress of the call along with the
call details and call content so that the system allows the
whole call to be shown on a Graphical User Interface (GUI)
with graphical indications of the current state of the call
and significant events within the call. The user can then
20   choose which section(s) of the call to play by clicking on
the appropriately marked points. Also, required segments of
the call to be presented in isolation and played
individually or one after the other.

25   The present system, through monitoring and recording the
progress of the call along with the audio content of the
call, advantageously allows speech recognition algorithms to
be directed at only those sections of conversations where
maximum value is likely to be obtained. For example, no
30   interpretation of the speech is undertaken whilst the
customer's address is being taken. Likewise, interpretation
can be concentrated on sections where sales objections are
being handled or likely to be handled. Further, the
algorithms can be directed in their selection of likely
35   words according to the context of the conversation. For
example, if a CSR has tabbed to the "Destination" field on
screen, the customer is therefore more likely to have said

13

"Paris" than "Pairs". Also, the algorithm can be directed
as to the likely speaker - whether CSR or customer.   That
is, where independent transmit and receive audio streams are
not available, the progress through the call can be used to
5   identify which speaker is most likely to be talking.

The capabilities described above also allow the system to be
used for the following additional and advantageous purposes.
Usability analysis can determine how many keystrokes/mouse
10 clicks were required to perform the most common functions
and also identify the most common functions. Testing and
Verification can also be achieved and used to find any calls
where an order was taken that had not previously taken the
customer through the required explanatory text thereby
15 identifying an invalid path through the call flow script.
CSR Quality Monitoring allows for the identification of
those CSRs that spend more, or less, time than expected in
specific sections of the call flow process or that follow
certain paths through the call flow more or less often than
20 the norm.

The invention is described further hereinafter, by way of
example only, with reference to the accompanying drawings in
which:
25   Fig. 1 is a block diagram of a recording and analysis
system embodying the present invention;
        Fig. 2 is a functional block diagram of a recorder such
as that in Fig. 1;
        Fig. 3 is a functional block diagram of an Application
30 Programming Interface (API) for use within an embodiment of
the present invention;
        Fig. 4 is an illustration of a graphical representation
of the progress of a call;
        Fig. 5 is a flow diagram such as that displayed in
35. accordance with ·an embodiment of the present invention to
illustrate call progress; and
        Fig. 6 is a further flow diagram derivable from the

14

diagram of Fig. 5.

Turning first to Fig. 1, one or more datastream recorders 4
are connected to speech transmission circuits 2 which in
5 turn are typically connected to a Private Automatic Branch
Exchange (PABX) or similar telephony switching system 1.
Connection is achieved by means of a high impedance tap 3
which does not impact the normal use of the speech paths but
also allows the recorder to monitor the signals on the
10 paths.

The recorders 4 are also connected to a local area network
such as an ethernet (7) over which they communicate with
other components of the system and can receive data for
15 storage along with the voice data that they are recording
from the speech paths (3). This data can be provided by any
application on the network such as central business
applications running on servers 6 or on an end user's
desktop 10.
20

A server 5 consolidates details of all calls recorded by the
recorders 4 which may be scattered across a local or wide
area network and maintains a central database of "call
records" which can be searched using standard SQL
25 techniques. This also maintains details of the current
location of removable media and the calls they contain.

Also running on a server 5 as part of the recording system
is typically an application, for example UNIFY, which
30 interprets Computer Telephony Integration (CTI) data from
the telephony switch 1. This information is used to control
the recorders 4 and indicate when to start and stop
recording on both the speech and data channels. This
information is also used to "tag" the calls with information
35 regarding the call, such as which extension 8 the call was
directed to. The recording of the data streams can also be
controlled by this application and these too can be tagged

with additional detail, such as which desktop 10 they relate
to. Additionally, data stream recordings can be tagged with
the identifier of the speech call that is in progress on the
same desktop. For example, data from desktop 10 would be
5 tagged with the identifier of the extension 8 on that
desktop.

The voice and data calls that have been recorded can be
retrieved by applications running on PCs on the network 11.
10 These applications search the call-details database held on
the server 5 to determine which call(s) they wish to replay
and where these calls are currently held. The call content
is then requested from the recorder holding the disk, tape
or optical media on which it has been stored.
15

The following components of an overall system are currently
available and are used as an underlying platform on which
the specific enhancements used to provide the benefits
described above can be deployed.
20

Multimedia Stream Recorders

The recorder (4) is an example of a multi-channel voice
recorder capable of storing up to 128 conversations
25 simultaneously. Fig. 2 shows the relevant details of the
recorder. The speech signals are presented via a high
impedance tap 12 and are typically compressed by an
appropriate line interface card 14. At regular intervals
the blocks of data to be stored are passed via the internal
30 data recording interface 16 for indexing and storage to hard
disk 18, or optionally, Digital Audio Tape (DAT) media for
longer term archive. Calls can be "tagged" with arbitrary
data fields describing the call and subsequently retrieved
for replay or analysis. In addition to recording voice
35 calls, the recorder can record data streams representing
arbitrary communication types. Examples include PC screen
capture recordings, messages for display on underground

16

trains in-cab displays etc. These are typically presented as Internet Protocol (IP) packets via an ethernet cable 13 connected to an appropriate Network Interface Card (NIC) 15. The contents of these packets are passed through the same
5   internal storage API 16 for storage to disk.

Computer Telephony Integration (CTI) Control and Tagging.

The UNIFY component mentioned above is used to interpret one
10 or more data streams typically provided by telephony switches, Automatic Call Distributors (ACDs) or applications within a call centre. By passing the information flows from these and applying customers defined rules, the UNIFY component will control the recorders to start, stop, pause,
15 resume or break recordings on specified voice and/or data channels and/or to "tag" recordings, current or past, with specified data. These data fields ultimately form part of that recording's call detail record and can later be used to search for it.
20

Enterprise-wide Recording and Retrieval Services

E-Ware is an example of a suite of NT 4.0 applications which manage one or more recorders to provide, across the
25 customer's local or wide area network, an enterprise-wide set of recording and retrieval services. Application Programming Interfaces (APIs) provide access to recording control, configuration, status monitoring, search and retrieval mechanisms. The system consolidates the call
30 detail records from all the recorders in the system into a central, open relational database allowing queries of arbitrary complexity to be performed using SQL. Additionally, the system records the contents and current location of all removable media to which calls have been
35 recorded.

Data Recording System

One of the APIs of systems such as E-Ware provides for data recording capabilities and can be used by screen capture mechanisms.

5   The generic data recording API 21 is implemented for example by Eware2DR.DLL on Windows platforms and allows applications 19 to:

- register data streams as being available for storage;

10   - start and stop recordings on such data streams with the data being transferred across the network 23 via IP packets formed by an IP protocol stack 22 and ultimately stored on the recorders (4);

- provide their own timing information within the
15   data stream supplied or have the system automatically package the data inside a protocol that adds time information at the required level of accuracy and granularity.

20 Replay Application

Windows applications such as "Replay Studio" can be provided that allow a user to:

- specify search criteria and perform searches to
25   select a required set of call details from the central database;

- view the results of these searches in tabular and/or graphical formats;

- retrieve the contents of selected calls from the
30   recording system for delivery to a local or shared cache area for subsequent replay; and

- replay one or more selected calls in a way appropriate to the type of call. Examples are voice calls played via a soundcard and screen
35   capture calls replayed in an on-screen window.

The application consists of an ActiveX framework into which

additional data visualisation and replay mechanisms can be
added to support new call types.

Call Flow Recordings (CFRs)

5

The particular features related to this embodiment of the
invention are as follows. The main purpose of these
enhancements is to provide a Call Flow Recording (CFR) that
details - to the level of detail required for a given
10 application - the progress of a call through the system.
this CFR is not a database record but is actually a
recording of a real-time data stream that allows the
progress of the call to be reconstructed including both the
route it took through the call handling process -
15 potentially down to the individual key-strokes entered - and
when each step occurred.

These CFRs are stored within the generic recording system as
"calls" of a new, well-known, Format type. This allows the
20 retrieval and replay tools to recognise them and display
them appropriately as opposed to trying to replay them as
audio calls. The format identifier used is chosen to be in
the range reserved for variable bit rate streams.

25 These CFRs are tied to the other components of the call,
such as voice recording and screen content record, by use of
cross-reference fields within their call detail records.
Each CFRs call detail record includes the globally unique
reference number of the "parent" call - typically a voice
30 recording - to which it refers.

Additionally, "Parent" and "Child" flag fields can be used
within the call detail records to alert applications to the
fact that the voice call in question has one or more
35 associated "calls" and, conversely, that the CFR has a
related parent call and should not be viewed in isolation.

19

An alternative embodiment merges the context or progress information with the main recording so that the recorded data stream is an amalgam of the original plus the state information. A simple packetisation protocol allows the
5 combined stream to be decoded into blocks of original and additional state information. This packetisation protocol may be further extended so as to include many different data streams within the single file. Any one or more of these streams may be extracted from the whole for subsequent
10 analysis or replay.

Explicit Context Notification

Where applications involved in the progress of calls through
15 the call centre are required to explicitly advise the recording system of the call's current state, this can be achieved by using an API which is layered on top of the generic data recording API. This "Call Flow Recording API" (CFR-API) provides the following functionality:
20   -   it advises that the call is entering stage N, and
               offers user definable parameters $P1...Pn$
               associated with this transition which are
               typically the name of the stage;
          -     it advises that the call is leaving stage N, and
25   offers user definable parameters $P1 ...Pn$
               associated with this transition which are
               typically the name of the stage; and
          -     it advises that the event E that is occurring e.g.
               a sale being made, and offers user definable
30   parameters $P1 ...Pn$ associated with this
               transition, for example the value of the sale).

It should be noted that several levels of detail can be stored since calls can enter multiple stages without leaving
35 a higher level one. For example, a sales call may generate the following calls to the API as it is handled:

20

- entering Customer Identification Stage;
  - entering Name Determination Stage;
    - entering Surname Determination Stage;
    - leaving Surname Determination Stage;
    - entering FirstName Determination Stage;
      - entering HelpScreen;
      - leaving HelpScreen;
    - leaving FirstName Determination Stage;
  - leaving Name Determination Stage;
  - entering Address Determination Stage; and
  - leaving Address Determination Stage.

Implicit Context Determination

In some cases it may be that not all of the applications involved in the handling of calls will be enhanced to provide the above-mentioned explicit notification of call progress. In such cases it may be necessary to infer the progress of the call from other sources such as screen capture, network (e.g. 'web') traffic and/or speech analysis of the voice records.

In such cases, these other data streams may be used as more or less satisfactory proxies for the missing or incomplete call flow recording. Three examples of how call progress can be inferred are given below.

These inferred call flow elements may be analysed in real time and merged into the overall call flow recording or may be determined at a later date by retrieving the data recording from which they are to be extracted.

First, the progress can be inferred from the key-strokes entered. As the entry of data via the keyboard is such a common and essential part of most call handling, keystrokes can be, by default, recorded as an integral part of the call flow recording for a given workstation. This is performed

using standard Microsoft Windows "hooks" that allow
applications to intercept all keystrokes. The related data
is then combined into the same recording as the explicit
notifications. In effect, these provide the lowest level of
5 granularity within the call flow recording, for example,
appearing as:

 - entering FirstName Determination Stage;
   - KeyHit="F1";
   - entering HelpScreen;
10   - KeyHit="Esc";
   - leaving HelpScreen;
   - KeyHit="T";
   - KeyHit="o";
   - KeyHit="m"; and
15 - leaving FirstName Determination Stage.

The second means of inferring call progress relates to mouse